


SPECIFICATIONS

Short Form Specs

Winston CVap Holding Cabinet, model HL4522-AL with electronic A-Series differential controls to provide precise food temperature from 90° F to 180° F (32° C to 82° C) and maintain food texture with settings labeled moist, soft moist, firm moist, and crisp. Utilizes Controlled Vapor technology (patent #5,494,690) as a method and apparatus for holding hot foods, consisting of an air heater and water heater to establish ideal water vapor content that is in relation with the moistness characteristics for the food. Uniflo airflow design provides even heat distribution. Utilizes circulating fan to assist heat recovery.

Construction

Control	Electronic differential control with dials labeled Food Temperature and Food Texture.
Capacity	14 Sheet Pan (18" x 26" x 1.25") 28 Steam Table Pan (12" x 20" x 2.5") 14 Gastronorm Pan 2/1
Weight Tolerance	65 lbs. (29.25 kg) per rack.
Electrical	Supplied with 84" (2,134 mm) (minimum) power cord and plug.
Shelving	Adjustable, wire racks (standard 3.5" (89 mm) centers (OC). Rack supports accommodate wire racks, sheet pans, gastronorm, or steam table pans.
Materials	To be commercial and institutional grade stainless steel interior and aluminum exterior to provide ease of cleaning and long service life with reasonable use and care.
Doors	Fully insulated aluminum exterior. Magnetic door latch.
Casters	Includes two locking, two non-locking, heavy duty, non-marking.
Water Fill	Operated manually. Low mineral potable water is recommended, otherwise use deionizer/demineralizer to minimize corrosive damage.
Installation Requirements	Allow at least 2" (51 mm) clearance on sides, particularly around ventilation holes. Allow at least 18" (457 mm) clearance from heat producing equipment, such as ovens or fryers. Generally this equipment does not need to be installed under a mechanical ventilation system (vent hood). Check local health and fire codes for requirements specific to your location. Unit must be installed at level.




HL4522-AL

CVAP HOLDING CABINET
Electronic Differential Control

**FULL SIZE MODEL, WITH FAN
ALUMINUM EXTERIOR (SHOWN)**





CVap® Holding Cabinets are designed for high quality holding of a wide variety of menu items for extended times. They can be used for proofing, holding, and serving.



Drawings not to scale

Drawings Not to Scale

capacity	size in (mm)	volts	hertz	ph	amps	watts	nema	ship wt. lb (kg)	ship cube						
14 SP 28 STP 14 GP 2/1	H3= 73.1" (1857) H5= 74.9" (1902) HT= 75.7" (1923) W= 27.6" (701) WT= 29.5" (749) D= 34.5" (876) DT= 37.6" (955)	US / CANADA													
		120	60	1	14.5	1730	US 5-15P 	370 (168)	C3,5=60.0 (1.7) CT=73.9 (2.1)						
							CAN 5-20P 								
		INTERNATIONAL													
		CALL FACTORY FOR INFORMATION.													

SP= Sheet Pan (18" x 26" x 1.25") • STP= Steam Table Pan (12" x 20" x 2.5") • GP= Gastronorm Pan • H3= Height w/3" casters • H5= Height w/5" casters
HT= Height w/transport or bumper guards • WT= Width w/transport or bumper guard • DT= Depth w/transport or bumper guard

CONTROLLED VAPOR TECHNOLOGY Exclusive Controlled Vapor technology (U.S. patent # 5,494,690) establishes that the water vapor content in the cabinet is the same as that of the food. This unique process controls moisture evaporation and saturation, so crisp foods stay crisp, and moist foods stay moist.

EASY-TO-USE CONTROLS Electronic differential controls are easy to understand and reliable. Never requires field calibration.
FOOD TEMP DIAL allows precise control of food temperature from 90 to 180°F (32 to 82°C).
FOOD TEXTURE DIAL maintains just-cooked texture with settings labeled moist, soft moist, firm moist, and crisp. No guesswork required.

BUILT TO LAST WITH QUALITY CRAFTSMANSHIP, high grade stainless steel interior, aluminum exterior, and full insulation on top, sides, and doors.

ALLOWS FOR BETTER CONTROL OF FOOD QUALITY, hold your menu items at just-cooked quality and precise serving temperatures for extended times.

INDUSTRY COMPLIANT, CVap equipment complies with domestic and international requirements such as UL, C-UL, UL Sanitation, CE, and others.

WARRANTY. Limited one year warranty. Warranty disclaimer for failure to clean. Ask for complete warranty disclosure.

SPECIFY THE FOLLOWING WHEN ORDERING:

Standard (No additional cost):

1. Voltage: 120V
*Inquire about additional international voltages available.
2. Hinge preference: Left or right
3. Casters: 3" (76") casters

Optional (Additional cost):

1. Casters: 5" (127 mm) casters
2. 6" (152 mm) legs
3. Window: Window in doors
4. Locking handle
5. Cord wrap
6. Drain ball valve
7. Control cover
8. Bumper guard
9. Transport package
10. Solid rack supports: Solid stainless steel rack supports (replaces standard wire rack supports)
11. Automatic water fill system
12. Extended warranty

Accessories & Supplies (Additional cost):

PS2206-4	Wire rack,chrome (Qty 4)
PS2206-5	Wire rack,chrome (Qty 5)
PS2938-4	Wire rack, SS (Qty 4)
PS2938-5	Wire rack, SS (Qty 5)
PS2553	8.5" (216 mm) Top cover extension
PS2351	11" (279 mm) Top cover extension
PS2696	Mobile water removal system
PS2429	External water filter (auto water fill units only)

FOR WINSTON SERVICE PARTS, ACCESSORIES, AND SUPPLIES ONLINE!

foodservice.winstonind.com/parts-supplies