

LP46 & LP56

Collectramatic® Pressure Fryer

SPECIFICATIONS

Short Form Specs	Winston Collectramatic high efficiency pressure fryer, model LP46 or LP56 with 20-channel processor controls and 13" deep collector, which allows up to 360 lbs. of chicken (or equivalent) to be cooked without manual filtration or emptying collector. Utilize quarter rack basket to maintain separation of product during cooking.				
Construction					
Control	Computerized processor control with twenty programmable channels.				
Capacity	LP46 4 Head - 14 lbs. (6.35 kg) product 64 lbs. (28.8 kg) or 8.15 g (30.85L) cooking oil LP56 6 Head - 18 lbs. (8.2 kg) product 75 lbs. (33.8 kg) or 9.55 g (36.15L) cooking oil				
Electrical	Refer to wiring schematic included in equipment for installation assistance. Cord/Plug not included. Shipped wired for 3-phase application. Licensed electrician may be required. Check local codes.				
Materials	To be 16 - 20 gauge stainless steel mounted on four adjustable legs. Cooking vessel to be constructed of stainless steel.				
Insulation	Full 1-1/2" insulation around the cooking vessel.				
Load Limits	Maximum of 14 lbs. (LP46) or 18 Lbs. (LP56) of frozen or refrigerated chicken, fish, meats, or vegetables per load.				
Installation Requirements	Ventilation required. Check local codes.				



LP46 & LP56 COLLECTRAMATIC® HIGH EFFICIENCY FRYER 20-Channel Programmable Controls



Collectramatic High Efficiency Pressure Fryers are the workhorses of any kitchen and can cook up to 120 deliciously golden-brown fried chickens without filtration.



C:ULECTRAMATIC

WINSTON FOODSERVICE

2345 Carton Drive | Louisville, KY 40299 USA winstonfoodservice.com | 800.234.5286 | +1.502.495.5400

Specifications subject to change without notice.

JOB	
ITEM#	



LP46 & LP56

Collectramatic® High Efficiency Pressure Fryer

		/ ι ε))) Power left sid 3" fron	' from e and		20.0" (508)	37.8" (960)	Power cord inlet 30.0" (762)	
capacity	size in (mm)	volts	hertz	ph	amps	watts	circuit amps	ship wt. lb (kg)	ship cube
4 Head 14 lbs. (6.35 kg)	H= 50.0" (1270) H2= 61.0" (1549) W= 20" (508) D= 30.0" (762)	208	60	3	29.2	10500	50		
		240	60	3	25.2	10500	50	190 (86)	20.0 (0.57)
		240	60	1	43.7	10500	60	,	
or 8.15 g (30.85L)		INTERNATIONAL							
cooking oil		400*	50	3	N/A	10500	N/A	190 (86)	call factory
		US / CANADA							
LP56 6 Head 18 lbs. (8.2 kg) product 75 lbs. (33.8 kg), or 9.55 g (36.15L) cooking oil	H= 50.0" (1270) H2= 61.0" (1549) W= 20" (508) D= 30.0" (762)	208	60	3	29.2	10500	50	207 (94) 20.0 (0.57)	
		240	60	3	25.2	10500	50		
		240	60	1	43.7	10500	60		
		INTERNATIONAL							
		400*	50	3	N/A	10500	N/A	207 (94)	call factory

H= Height w/lid closed • H2= Height w/lid open • Includes: 1 clamshell basket, 1 drain hook, 1 pair gloves, 1 spatula, 2 collector gaskets, 2 lid gaskets, 1 Teflon* brush, 1 long collector, 1 heat plate • Cord and plug not included

OPERATIONAL EXCELLENCE the Collectramatic fryer has the largest cold zone in the industry and can perform 20-30 cook cycles without filtration, which extends shortening life and reduces filtering downtime. If speed of service is important, the fryer's heat curve can be adjusted to cook up to 18 lbs. of fried chicken in as little as ten minutes. Utilizing Winston's Quarter Rack basket system improves labor efficiencies because the chicken is cooked on racks and moved directly into the holding cabinet with minimal handling.

EASY-TO-USE CONTROLS standard to all Collectramatic fryers is a microprocessor control, which never requires calibration for accuracy. Within any of the twenty channels, up to six temperatures and multiple time settings can be programmed per cook cycle. The controller also offers "Flex-Time" for varying sized products and a shortening management system.

BUILT TO LAST WITH QUALITY CRAFTSMANSHIP, the cylindrical cooking pot of the Collectramatic fryer is constructed to last for many years. Each fryer is built with high grade stainless steel and uses very few moving parts.

WARRANTY. Limited one year warranty. Warranty disclaimer for failure to clean. Ask for complete warranty disclosure.



COLLECTRAMATIC

WINSTON FOODSERVICE 2345 Carton Drive | Louisville, KY 40299 USA winstonfoodservice.com | 800.234.5286 | +1.502.495.5400

Specifications subject to change without notice.

SPECIFY THE FOLLOWING WHEN ORDERING:

- Standard (No additional cost):
 - 1. Model number.
 - 2. Voltage Preference: 208V or 240V for US or Canada.
 - 3. Drain Valve Indicator
 - Cordset is not included.
 - All units shipped 3-phase.

*Inquire about additional international voltages available.

Standard (No additional cost):

- 1Clamshell basket1Drain Hook2Collector gaskets1Heat plate2Lid gaskets1Teflon® brush1Spatula1Long collector
- 1 Plugging tool

1 Displacer tool

Accessories & Supplies (Additional cost):

PS1180	Utensil rack	PS2837/25Qtr rack basket shelves
PS2838	Qtr rack basket, 4-hd	PS1290 Open basket
PS2839	Qtr rack basket, 6-hd	PS2837/1 Qtr rack basket shelf
PS2837/10	Qtr rack basket shelves	PS2837/50 Qtr rack basket shelves

FOR WINSTON SERVICE PARTS, ACCESSORIES, AND SUPPLIES ONLINE! foodservice.winstonind.com/parts-supplies